
RAY-BAR FIRE RATED VISION WINDOWS FOR WOOD OR HOLLOW METAL FIRE RATED DOORS

IT IS THE RESPONSIBILITY OF THE CUSTOMER TO VERIFY AND CONFIRM FIRE RATING REQUIREMENTS PRIOR TO ORDERING



MAXIMUM CLEAR VIEW "DAYLIGHT" GLASS OPENING SIZES PERMITTED FOR FIRE RATED DOORS

	1/4" WIRELITE - NT GLASS						1/4" WIRELITE-NT GLASS with PEMKO FG3000 FIRETAPE				3/16" FIRELITE-NT (Film) or 5/16" FIRELITE+PLUS (Lami)			
	RATING (MINUTES)	MAX WIDTH	MAX HEIGHT	MAX SQ. INCH PER LITE	MAX SQ. INCH PER LEAF	MAX WIDTH	MAX HEIGHT	MAX SQ. INCH PER LITE	MAX SQ. INCH PER LEAF	MAX WIDTH	MAX HEIGHT	MAX SQ. INCH PER LITE	MAX SQ. INCH PER LEAF	
	20	34-1/2	92	3,289	2400	34	84	2856	2856	36	89	3204	3204	
	45	54	54	1296	2400	34	84	2856	2856	36	89	3204	3204	
	60	10	33	100	100	12	80	960	1716	36	89	3204	3204	
	90	10	33	100	100	12	46	552	1716	36	56-1/2	2034	2034	
	180	ı	-	-	-	-	ı	-	-	12	33	100	100*	
		* CUSTOMER MUST ALSO VERIFY DOOR FIRE TESTING SIZE LIMITS *												
₩	60 *	-	-	-	-	-	ı	-	-	12	33	100	100*	공류
RISE,	90 *	-	-	-	-	-	1	-	-	12	33	100	100*	TEMP
	1/4" WIRELITE -NT GLASS WIREGLASS WITH SAFETY FILM						1/4" WIRELITE-NT GLASS W/ PEMKO FG 3000 FIRETAPE				3/16" FIRELITE-NT OR 5/16" FIRELITE + PLUS			

- * TEMPERATURE RISE ALL FIREGLASS LISTED IS IMPACT RESISTANT
- **UL FILE R38927**
- WIRELITE-NT IS SAFETY FILMED
- FIRELITE-NT IS SAFETY FILMED
- FIRELITE + PLUS IS LAMINATED
- VISION FRAMES ARE STANDARD
- FLUSH INTEGRAL VISION LITES OPTIONAL
- WIRELITE-NT, FIRELITE-NT AND FIRELITE+PLUS ARE ALL IMPACT RESISTANT AND MEET ANSI Z97.1 AND CPSC REQUIREMENTS
- FIRE RATED INSULATED GLASS UNITS

Terms of Use: Certain designs and concepts are the exclusive proprietary property and work product of Ray-Bar Engineering provided in good faith as a courtesy for the architectural design of projects specifying, incorporating and utilizing genuine Ray-Bar products and assemblies. Ray-Bar designs are not to be copied, altered, plagiarized or utilized in any competitive or detrimental manner against Ray-Bar as protected by law and/or copyrights. "All Rights Reserved"

© 2019 Ray-Bar Engineering Corporation. * Ray-Bar is a registered trademark of Ray-Bar Engineering Corp. * FireLite and FireLite Plus are registered trademarks of NEG Co, Ltd.
* Pilkington Pyrostop is a registered trademark of Pilkington plc. * WireLite and Fireglass are registered trademarks of TGP. * For additional information and details please contact Ray-Bar

ENGINEER					
8	JOB NAME:				
E COR	LOCATION:				
	ROOM NUMBER:				
U.S.A.	SHEET OF:				
RAY-BAR FIRE RATED VISION LITES FOR DOORS					

RAY-BAR ENGINEERING CORP.

Toll Free: 1(800) 444-XRAY / 1(800) 444-9729

Telephone: (626) 969-1818 24 Hour Fax: 1(800) 333-XRAY /

1(800) 333-9729

www.raybar.com

RAY-BAR FIRE RATED VISION LITES

RB-FRD