RAY-BAR ENGINEERING CORPORATION

TECHNICAL DATA FIRELITE[®] CERAMIC FIRE GLASS

MAXIMUM SIZE LIMITS

Product Trade Name: FIRELITE® (UL) us

ASSIFIE

3/16" FIRELITE[®] 3/16" FIRELITE[®]-NT and 5/16" FIRELITE[®]+ PLUS

It is the responsibility of the customer to verify and confirm fire rating requirement prior to ordering.



SIZES IN MAXIMUM VISIBLE EXPOSED AREA LIMITS DAYLIGHT VIEW

Please note the following points.

- UL Listed/Classified and permanently labeled, with required hosestream test.
- Standard stock sizes available up to 48" x 96".
- Safety Glass available upon request, permanently labeled meeting ANSI Z97.1 and CPSC 16 CFR 1201 Cat II requirements for impact resistance. Safety Glass is required in door vision lites and windows that occur within 24" of a door opening or within 36" of floor. Safety Glass is NOT tempered, impact-proof, shatter proof or scratch resistant.
- For impact resistance: FIRELITE-NT (filmed) or FIRELITE + PLUS (laminated).
- Available in IGU for Low-E, Tinted, Reflective, 1-Way Mirror and X-Ray Protective.
- UL File R38927, Testing to UL 9, UL 10C, NFPA 80, NFPA 252, NFPA 257, CAN4 S-104 and CAN4 S-106.

MAXIMUM SHEET SIZE OF ALL FIRELITE PRODUCTS IS 48"X96"

• For Fire Resistive, Radiant and Conductive Heat Barrier utilize PILKINGTON PYROSTOP[®]Glass (Meeting ASTM E-119 and UL 263).

RAY-BAR ENGINEERING CORPORATION WWW.RAYBAR.COM

LIFE AND SAFETY PRODUCTS



RADIATION • FIRE • BALLISTICS • BLAST •
 PH: (800) 444-9729 E-MAIL: SALES@RAYBAR.COM FAX: (800) 333-9729
"WHEN PROTECTION IN REQUIRED. THERE IS NO SUBSTITUTE FOR SKILL AND EXPERIENCE"

© 2019 Ray-Bar Engineering Corporation. * Ray-Bar is a registered trademark of Ray-Bar Engineering Corp. *FireLite and FireLite Plus are registered trademarks of NEG Co, Ltd. * Pilkington Pyrostop is a registered trademark of Pilkington plc. * WireLite and Fireglass are registered trademarks of TGP. * For additional information and details please contact Ray-Bar.