

RAY-BAR FIRE GLASS GLAZING TAPE

FOR 20 MIN, 45 MIN, 90 MIN, 120 MIN AND 180 MINUTE GLAZING APPLICATIONS




BLACK CLOSED CELL PVC FOAM GLAZING FIRE TAPE

3/8" WIDE X 1/16" THICK TAPE  3/8" 1/16"

OR

3/8" WIDE X 1/8" THICK TAPE  3/8" 1/8"

- 20, 45, 60, 90, 120 AND 180 MINUTE
- UL 10C POSITIVE PRESSURE
- ADHESIVE BACKED "PEEL AND STICK" INSTALL



BLACK INTUMESCENT FIRE TAPE

1/2" WIDE X 1/16" THICK TAPE  1/2" 1/16"

- FOR WIRE GLASS RATED 45, 60 AND 90 MINUTE



PEMKO FG3000-S-45 FIRE TAPE

7/16" WIDE X 3/64" THICK TAPE  7/16" 3/64"

- 20 AND 45 MINUTE RATED
- MEETS UL 10C POSITIVE PRESSURE
- UL CLASSIFIED PRODUCT 1S47



- **MUST BE UTILIZED WITH ANY 45 MINUTE WIRELITE-NT EXPOSED AREA EXCEEDING 1,296 OR IF EXCEEDING 53"+ HIGH, OR IF EXCEEDING 53"+ IN WIDTH (OR GREATER)**



PEMKO FG3000-S-90 FIRE TAPE

7/16" WIDE X 3/64" THICK TAPE  7/16" 3/64"

- 20, 45, 60 AND 90 MINUTE FIRE RATED
- MEETS UL 10C POSITIVE PRESSURE
- UL CLASSIFIED PRODUCT 1S47

- **MUST BE UTILIZED WITH ANY 90 MINUTE WIRELITE-NT EXPOSED AREA EXCEEDING 1,296 OR IF EXCEEDING 53"+ HIGH, OR IF EXCEEDING 53"+ IN WIDTH (OR GREATER)**



KERAFIX 2000 FIRE TAPE (WHITE)

1/2" WIDE X 1/8" THICK TAPE  1/2" 1/8"


- MEETS UL 10C POSITIVE PRESSURE

- **MUST BE UTILIZED WITH ANY 90 MINUTE RATED FIRELITE CERAMIC GLAZING EXCEEDING 1,393 SQ.INCH EXPOSED CLEAR VIEW DAYLIGHT (OR GREATER+)**

➔ HIGHER RATED FIRE TAPE MAY BE UTILIZED IN LOWER RATED FIRE RATING ASSEMBLIES ➔

FOR MORE INFORMATION VISIT : WWW.FIREPROOFGLASS.COM

Terms of Use: Certain designs and concepts are the exclusive proprietary property and work product of Ray-Bar Engineering provided in good faith as a courtesy for the architectural design of projects specifying, incorporating and utilizing genuine Ray-Bar products and assemblies. Ray-Bar designs are not to be copied, altered, plagiarized or utilized in any competitive or detrimental manner against Ray-Bar as protected by law and/or copyrights. "All Rights Reserved"

	JOB NAME:
	LOCATION:
	ROOM NUMBER:
	SHEET ____ OF ____:
	RAY-BAR GLAZING FIRE TAPE TYPES

RAY-BAR ENGINEERING CORP. Toll Free: 1(800) 444-XRAY / 1(800) 444-9729 Telephone: (626) 969-1818 24 Hour Fax: 1(800) 333-XRAY / 1(800) 333-9729 WWW.RAYBAR.COM	RAY-BAR GLAZING FIRE TAPE PRODUCTS
--	---